


RKS



Rundkabelhalter, steckbar
Plug-in round cable holders



Art.-Nr.	Artikel-Bez.	KD ø	B _{CH} ø	MS _{CH}	L	W	W2	Höhe	Farbe
05529	RKS-064/20-G	6,4	6,4	2,0-3,8	25,4	14,7	10,4	11,2	■
05534	RKS-095/38-G	9,5	6,4	2,0-3,8	25,4	16,5	12,7	12,7	■
NEW 39650	RKS-095/27-N	9,5	6,5-7,0	0,6-2,7	23,9	14,4	14,4	15,0	□
16657	RKS-105/16-N	10,5	6,5	0,8-1,6	25,7	16,8	11,8	15,0	□
NEW 39649	RKS-127/27-N	12,7	5,0-6,0	0,6-2,7	31,8	19,0	16,0	18,4	□
03493	RKS-190/20-G	19,0	6,4	0,5-2,0	35,1	22,4	17,1	24,6	■
NEW 39651*	RKS-250/16-N*	25,0	6,5	0,8-1,6	38,7	9,5	9,5	30,0	□
NEW 39652*1	RKS-300/20-N*1	30,0	6,5	0,8-2,0	43,0	9,5	9,5	36,0	□


*Bauform ähnlich zu Skizze · 1abweichende Brandklasse UL-94 V-0 · Unit: mm · MOQ 100x

Standard-Material: PA UL-94 V-2 □ natur -40°C bis +75°C
PA UL-94 V-2 ■ hellgrau (G) -40°C bis +75°C

RKSV



Rundkabelhalter, steckbar
Plug-in round cable holders



Art.-Nr.	Artikel-Bez.	KD ø	B _{CH} ø	MS _{CH}	L	W	Höhe	Farbe
26490*	RKSV-070095/16-N	7,0-9,5	6,4*	0,8-1,6	22,0	12,2	24,1	□
NEW 42824	RKSV-079102/15-N	7,9-10,2	6,4	0,8-1,5	19,1	8,2	21,5	□
26491	RKSV-119143/15-N	11,9-14,3	6,4	0,8-1,5	31,5	10,2	29,8	□
00981	RKSV-147191/15-N	14,7-19,1	6,4	0,8-1,5	38,1	12,7	34,5	□

*siehe Montagebohrung für Artikel: 26490 · Unit: mm · MOQ 100x

Standard-Material: PA UL-94 V-2 □ natur -40°C bis +75°C
Material auf Anfrage: PA UL-94 V-0 □ natur -40°C bis +75°C

Montagebohrung für Artikel: 26490
Mounting Hole for item: 26490

